

PRODUCT: **1007 PREDATOR CARB CLEANER 347g**

SECTION 01: IDENTIFICATION

24 hour emergency telephone number..... CHEMTREC 1-(800) 424-9300

Recommended Use..... Carburetor cleaner

SECTION 02: HAZARD IDENTIFICATION



SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS		
CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Acetone	67-64-1	65-85
Heptane (includng isomers)	64742-49-0	5-10
Carbon dioxide	124-38-9	3-7

PRODUCT: Brake Buddy Brake Cleaner - 369 g (13 oz.)

SECTION 04: FIRST-AID MEASURES If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain Inhalation..... immediate medical assistance. If breathing is difficult, give oxygen and get medical attention. Do not give adrenaline, epinephrine or similar drugs following exposure to this product. Wash thoroughly with soap and lukewarm water. Skin Contact..... Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the Eye Contact..... upper and lower eyelids. Get medical attention if irritation persists. Do not induce vomiting, get medical attention. Consult poison control center or physician Ingestion..... IMMEDIATELY. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Provide general supportive measures and treat symptomatically. In case of shortness of Most important symptoms/effects, acute ... and delayed Indication of immediate medical attention and special treatment needed breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Unsuitable Extinguishing Media Specific Hazards Arising from the Chemica	Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire. al Contents under pressure. Pressurized container may explode when exposed to heat or
	flame.
Special Protective Equipment and Precautions for Firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. For massive fire in cargo area, use
General Fire Hazards	unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Extremely flammable aerosol.
General i lie i lazal 05	

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/national regulations (see section 13). Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.
Environmental Precautions	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling	missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid contact with eyes, skin, and clothing. Avoid breathing vapour of this product. Avoid contact with skin and eyes. Avoid prolonged exposure. Use in well-ventilated areas.
Conditions for Safe Storage including any Incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials (see Section 10).

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	AC TWA	CGIH TLV STEL	OSH PEL	IA PEL STEL	NIOSH REL
Acetone	250 ppm	500 ppm	1,000 ppm (2,400 mg/m3)	Not available	Not available
Heptane (includng isomers)	1,600 mg/m3 (RCP-TWA)	Not available	Not available	Not available	Not available
Carbon dioxide	5000 ppm	30000 ppm	9000 mg/m3	Not available	STEL: 30000ppm; TWA: 5000ppm

Appropriate Engineering Controls.....

Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved.

PRODUCT: Brake Buddy Brake Cleaner - 369 g (13 oz.)

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

Do not get in eyes. Wear safety glasses with side-shields.
Chemical resistant gloves are recommended. Avoid contact with the skin. Wear appropriate chemical resistant clothing.
· · · · · · · · · · · · · · · · · · ·
Use dust and mist respirator.
None Known.
When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Physical Odor	Appearance eshold (ppm) Gravity	Acetone-like.
Aerosol V pH Boiling P Melting/F Flash Po Flashbac Evaporat VOC Cor Solubility Aerosol F Auto Igni Lower Fla Upper Fla Coefficie	/apour Pressure (psig, 21°C) Density (Air=1) ioint liquid (°C) reezing Point (°C) int (°C), Method k ion Rate (n-Butyl Acetate = 1) thent lame Projection lame Projection tion Temperature (°C) ammable Limit (% Vol) ammable Limit (% Vol) ht of Water/Oil Distribution	- 95°C (- 138°F). (Acetone). -9. (ASTM D-56). (Heptane). No data . N/A. <10%. Nil. No data. 265. (Heptane).

SECTION 10: STABILITY AND REACTIVITY

Reactivity Chemical Stability
Possibility of Hazardous Reactions
Conditions to Avoid
Incompatible Materials Hazardous Decomposition Products
Hazardous Decomposition Products

Product not reactive under normal conditions of use. Material is stable under normal conditions. Will not occur. Avoid sources of heat and flame, and electrostatic charge. Strong oxidizing agents. Strong acids. Carbon Oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Acetone	71 mg/L (Rat - 4 hrs)	5,800 mg/kg (Oral - Rat); >15,800 mg/kg (Dermal - Rabbit)
Heptane (includng isomers)	>23.3 mg/L (Rat - 4 hrs)	>5,840 mg/kg (Oral - Rat); >2,920 mg/kg (Dermal - Rat)
Carbon dioxide	Not available	Not available
Routes of entry - Skin & Eye Routes of entry - Ingestion Routes of entry - Skin Absorption Symptoms Related to the Physical, Chemical and Toxicological Characteristics Acute Toxicity Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation	itant effects. Symptoms may include stinging, teari sion. Defatting of the skin. Symptoms of overexpos edness, nausea and vomiting. oxic if inhaled. auses skin irritation. auses eye irritation. halation may cause respiratory tract irritation. o information is available. one known.	

PRODUCT: Brake Buddy Brake Cleaner - 369 g (13 oz.)

SECTION 11: TOXICOLOGICAL INFORMATION

STOT - Single Exposure	Specific target organ toxicity single exposure Category 3. May cause drowsiness and dizziness.
STOT - Repeated Exposure Aspiration Hazard	
	pneumonitis, which can be fatal.
Chronic Effects	Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity	May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment. Acetone (CAS#: 67-64-1): Toxicity to fish: LC50 >100 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: 10294 mg/L, 48 hrs; Toxicity to algae: not available . Heptanes including isomers (CAS#: 64742-49-0): Toxicity to fish: LL50 > 13.4 mg/L, 96 hrs; Toxicity to other aquatic invertebrates: EL50 3 mg/L, 48 hrs; Toxicity to algae: EL50 10-30 mg/L, 72 hrs. Chronic Toxicity Daphnia magna: NOEC 0.17 mg/L 21 days.
Persistence and degradability Bioaccumulation Potential Mobility in Soil Other Adverse Effects	The product itself has not been tested. The product itself has not been tested. The product itself has not been tested.

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Dispose in accordance with local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
DOT (US-Road)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D.
	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.
IATA (International- Air)	UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

SECTION 15: REGULATORY INFORMATION

Canada Regulations: Domestic Substances List (DSL) US Regulations	. Yes.
---	--------

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
Prepared by Latest Revision	