



# KOOL WELL™

## ADVANCED COOLANT CONDITIONER

Antifreeze becomes depleted of essential additives if not properly maintained. KOOL WELL™ not only replaces depleted inhibitors, but adds a long lasting alkaline reserve to the coolant. KOOL WELL™ protects against pitting, scaling and corrosion damage as well as providing maximum heat transfer from coolant. KOOL WELL™ is compatible with all types of coolant, and protects all metal and aluminum parts.

800-890-7935

### Directions:

Clean cooling system prior to treatment with Well Worth's FLUSH WELL™ Radiator Flush.

1. With engine off and cool, remove radiator cap. DO NOT REMOVE CAP WHEN ENGINE IS HOT.
2. Be certain water level is at least two inches below the overflow level. Add entire 12 oz bottle of KOOL WELL™ to the radiator.
3. Replace radiator cap. Run engine for at least 10 minutes. Bringing the coolant to operating temperature helps mix the product thoroughly. For preventative maintenance, add annually or whenever added protection is desired.

### Product Number and Packaging:

#8004 – 12 oz 12/CS



### **WARNING** KEEP OUT OF REACH OF CHILDREN

**PROTECTIONS:** Rubber or vinyl gloves and goggles are recommended.

**FIRST AID:** IF IN EYES: Flush with large amount of water for 15 minutes. IF ON SKIN: Wash with soap and water. INHALATION: Remove victim to fresh air. INGESTION: Do not induce vomiting. Give several glasses of water. Get medical attention.

**STORAGE:** Store in cool, dry and well-ventilated place. Wash empty container and discard in trash or recycle.