



DULL ALUMINUM LACQUER SPRAY PAINT



Professional formula auto paint provides superior coverage in a durable finish that won't crack, chip or peel. Use on metal, wood, fiberglass, automotive engines or anywhere a quality coating is desired. Our premium paints are lead-free and containing no ozonedepleting chemicals. Fast dry formula enables you to touch painted surfaces in a little as 15- 20 minutes.

800-890-7935

www.wellworthproducts.com

Directions:

1. Surface must be clean, dry, and free of rust before painting. Protect surrounding area from spray mist. For best results use when can is between 50°F and 90°F (10°C and 32°C)
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25 cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead ¼ turn or remove and clean sprayhead slot. Do not stick pin or other object into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Product Number and Packaging: #4007 – 12/CS

Contains: Acetone 67-64-1, Propane 74-98-6, Toluene 108-88-3, N-Butane 106-97-8, Calcium Carbonate 1317-65-3, Aluminum Flake 7429-90-5, Xylene 1330-20-7, Mineral Spirits 64742-47-8, Butyl Acetate 123-86-4, Isobutyl Acetate 110-19-0. OTHER INGREDIENTS: "Contents Partially Unknown", MMA-BMA-MAA Copolymer 28262-63-7.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.



Prevention: Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

Response: In case of fire, use fire extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have a product label at hand. IF IN EYES: Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. IF SWALLOWED: Rinse mouth with water. Do not induce vomiting. IF INHALED: Remove to fresh air. IF ON SKIN: Wash thoroughly with water. Remove all contaminated clothing.

Storage: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of product in accordance with local /regional /national/international regulations.

Additional Precaution Statements: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.